

OPERATING INSTRUCTIONS FOR THE WEBASTO HOLLANDIA 100 SUNROOF

Dear Webasto Customer,

Webasto wishes you much pleasure when driving with your newly installed Hollandia 100 tilting sunroof. Your sunroof is a quality product from Webasto, The Netherlands.

Below you will find all you need to know about the Webasto Hollandia tilting sunroof. In order to obtain the maximum enjoyment from the sunroof, please read these instructions carefully. Wishing you happy motoring from Webasto.

MAINTENANCE

GLASS PANEL

On the underside of the safety glass panel a coating has been applied to reduce the transmission of heat. If necessary you may clean the glass using a non-abrasive cleaning agent.

When starting your journey you are advised not to open the sunroof if there is moisture on the glass panel. Please drive for a few minutes to ensure that all the moisture has dissipated, then open the roof. SEALING

The glass panel fits against a wear-resistant rubber seal in order to make the sunroof watertight. In order to keep the rubber seal free from dust, dirt and debris, clean with a moist softcloth. The application of talcum powder extends the life of the seal.



Hollandia 100 Classic Latch

Pulling and pushing the latch handle operate the glass panel. There are six different open positions into which the glass panel can be adjusted.



Hollandia 100 DeLuxe Latch

Pulling and pushing the latch handle operate the glass panel. There are four different open positions into which the glass panel can be adjusted.



Hollandia 100 DeLuxe Rotary

Turning the rotary operate the glass panel. The glass panel can be positioned in any tilt position up to 74 mm.